

DRYER DATA SHEET

Refrigerant Dryers

MODEL DATA				
1	Manufacturer	HANKISON		
2	Date	6-13-22		
3	Model Number	FLX10.1		
4	Cycling/Non-Cycling	Cycling		
5	Refrigerant Type	R407C		
6	Air/Water Cooled	Air Cooled		
7	Voltage	460V - 3PH - 60HZ		
	DESCRIPTION	FULL FLOW	10% FLOW	UNITS
8	Tested Flow	1000	100	scfm ^b
9	Outlet Pressure Dewpoint	39.9	36.3	°F
10	Pressure Drop	4.26	.09	psi(d)
11	Total Dryer Input Power	5.84	.63	kW
12	Specific Package Power ^c	.59	.63	kW/100 scfm

- Inlet Compressed Air Temperature: 100°F (38°C)
- Inlet Compressed Air Pressure: 100 psig (7 Bar)
- Max. Ambient Air Temperature: 100°F (38°C)
- Inlet Compressed Air Relative Humidity: 100% (Saturated)

b. SCFM defined as the volume of free air in cubic feet per minute measured at 14.5 psia (1.0 Bar), 68°F (20°C) temperature and 0% R.H. (0 WVP).

c. (Total Dryer Input Power/tested flow) x 100

Member



This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.

Consult the CAGI website, www.cagi.org, for a list of participants in the third party verification program.